SCISSOR LIFT DS 12 18RT

- ✓ 4X4 WHEEL DRIVE
- ✓ DRIVE AT FULL HEIGHT
- ✓ GRADEABILITY 40%
- ✓ EXTENSION DECK
- ✓ NON-MARKING TIRES
- ✓ SOCKET IN BASKET
- ✓ SWING AXLE
- ✓ AUTOMATIC LEVELING

TECHNICAL SPECIFICATIONS

Working height	12.00 m
Platform height	10.00 m
Length	3.84 m / 3.19 m
Width	1.76 m
Height (Rails up)	2.59 m
Height (Rails down)	1.82 m
Platform length x width	2.88 m x 1.52 m
Platform extension	1.43 m
Ground clearance	0.24 m
Wheelbase	2.29 m
Load capacity	454 kg
Load capacity on platform extension	136 kg
Max number of persons	4 Persons
Turning radius (inside / outside)	2.15 m / 4.85 m
Driving speed (retracted)	5.20 km/h
Driving speed (extended)	0.48 km/h
Weight	4,300 kg / 3,900 kg
Motor	Kubota D1105 18.6 kw / 2,400 rpm
Hydraulic tank	71 Liters
Diesel tank	47 Liters
Rental number	981209

TELESCOPIC HANDLERS



COLLE RENTAL & SALES 00800 - 3625 3625 NFO@COLLE.EU WWW.COLLE.EU Follow us: @ D 1 1 m

Disclaimer: No rights can be derived from the texts, specifications, images, or other information found in this data sheet. Everything in this data sheet is subject to change. Photographs, texts, and specifications are approximations and are non-binding. During the design and creation of this data sheet, we worked as carefully as possible. However, we provide no guarantee that the information in this data sheet is complete, current, and/or accurate.