



## Specifications

Model	GS-3384 RT	
Measurements	US	Metric
Working height maximum*	39 ft	12.06 m
<b>A</b> Platform height maximum	33 ft	10.06 m
<b>B</b> Platform height - stowed**	5 ft 1 in	1.55 m
<b>C</b> Platform length:		
outside, extended - single deck	13 ft .5 in	3.98 m
outside, extended - dual deck	17 ft 6.25 in	5.34 m
<b>D</b> Slide-out platform extension deck - front	5 ft	1.52 m
<b>E</b> Slide-out platform extension deck - rear	4 ft	1.22 m
<b>F</b> Platform width - outside	6 ft	1.83 m
<b>G</b> Height - stowed:folding guardrails	8 ft 9.5 in	2.68 m
rails lowered	6 ft 6.75 in	2.0 m
<b>H</b> Length - stowed: single deck	12 ft 11.25 in	3.94 m
dual deck	13 ft 5 in	3.98 m
with outriggers	16 ft	4.88 m
<b>I</b> Width: standard tires	7 ft	2.13 m
high flotation tires	7 ft 11 in	2.41 m
<b>A</b> Wheelbase	9 ft 4 in	2.84 m
<b>k</b> Ground clearance - center	13 in	.33 m

## Productivity

Maximum platform occupancy	7	7
Lift capacity	2,500 lbs	1,134 kg
Lift capacity - extension deck	500 lbs	227 kg
Drive speed - stowed	4.0 mph	6.4 km/h
Drive speed - raised	0.7 mph	1.1 km/h
Gradeability - stowed***	50%	
Maximum outrigger leveling: front to back	7°	
side to side	12°	
Turning radius - inside	10 ft 1.5 in	3.09 m
Turning radius - outside	19 ft 6 in	5.94 m
Raise/lower speed	45/29 sec	
Controls	proportional	
Drive	four wheel	
Tires - foam-filled rough terrain	10 x 31 in	25 x 79 cm

## Power

Power source	Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW)
	Deutz D2011L03i 3 cylinder diesel 49 hp (36 kW) air cooled
Auxiliary Power unit	12 V DC
Fuel tank capacity	30 gal 113.6 L
Hydraulic system capacity	30 gal 113.6 L

## Weight\*\*\*\*

	12,005 lbs	5,445 kg
with outriggers	13,680 lbs	6,205 kg

## Standards Compliance

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Based on RT tires. Deduct 2 in (5.8 cm) for turf and non-marking.

\*\*\* Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

\*\*\*\* Weight will vary depending on options and/or country standards.

### Features

#### Standard Features

##### Measurements

- 39 ft (12.06 m) working height
- Up to 2,500 lbs (1,134 kg) lift capacity

##### Productivity

- 156.5 x 72 in (3.98 x 1.83 m) steel frame platform
- 60 in (1.52 m) extension deck
- Replaceable aluminum deck
- Folding guardrails
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Full height swing gate
- Two self-closing gates
- 4WD
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires (eco fill)
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter

##### Power

- 49 hp (36kW) Deutz D2011L03i diesel, Tier 4i

#### Options & Accessories

##### Productivity Options

- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Automatic leveling hydraulic outriggers
- Air line to platform
- Foam filled non-marking rough terrain tires 10 x 31 in (25 x 79 cm)
- High flotation air-filled tires 17 x 33 in (43 x 84 cm)
- High flotation foam-filled tires 16 x 33 in (41 x 84 cm)
- Dual flashing beacons
- Motion alarm
- Biodegradable hydraulic oil

##### Power Options

- 75 hp (56 kW) Ford DSG-423 gas/LPG
- AC, 2000 Watt generator (120 V / 60 Hz)
- Cold weather package
- Hydraulic oil cooler
- Diesel catalytic scrubber muffler
- LPG steel tank only, 33.5 lb capacity
- Welder ArcPro 275 heavy duty (includes hydraulic oil cooler)
- Welder ready package (includes hydraulic oil cooler)



#### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

#### Distributed By:

Effective Date: January, 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2014 Terex Corporation.