

Features

STANDARD FEATURES

MEASUREMENTS

GS™-3390

- 39 ft (12.06 m) working height
- Up to 2,500 lb (1,134 kg) lift capacity

GS™-4390

- 49 ft (15.11 m) working height
- Up to 1,500 lb (680 kg) lift capacity

GS™-5390

- 59 ft (18.15 m) working height
- Up to 1,500 lb (680 kg) lift capacity

PRODUCTIVITY

- 156.5 x 72 in (3.98 x 1.83 m) steel platform
- 60 in (1.52 m) extension deck
- Diamond plate deck
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Two self-closing gates
- Diamond plate deck
- 4WD
- Automatic leveling hydraulic outriggers
- Oscillating axle
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter

POWER

- 12 V DC auxiliary power

OPTIONS & ACCESSORIES

PRODUCTIVITY

- Oscillating axle (standard on GS-3390, optional on GS-4390 and GS-5390)
- Automatic leveling hydraulic outriggers (optional on GS-3390 and GS-4390, standard on GS-5390)
- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Air line to platform
- Pipe cradle (pair)
- Non-marking rough terrain tires 22 x 33 (30 x 84 cm)
- High flotation foam-filled tires 16 x 33 (41 x 84 cm)
- High flotation air-filled tires 16 x 33 (41 x 84 cm)
- Dual flashing beacons
- Motion alarm
- Platform work lights

POWER OPTIONS

- Ford gas/LPG 75 hp (56 kW)
- Deutz diesel 49 hp (36 kW)
- 3000 AC Watt generator (120V/60Hz)
- 2500 AC Watt generator (120V/50Hz or 240V/50Hz)
- Cold weather package
- Arctic package
- Hydraulic oil cooler
- Diesel scrubber/spark arrestor
- Diesel spark arrestor (without scrubber)
- LPG steel tank only, 33.5 lb capacity
- LPG tank kit (carrier with tank)



Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730
Telephone **+1 (425) 881-1800**
Toll Free in USA/Canada **+1 (800)-536-1800**
Fax +1 (425) 883-3475

Genie Europe

Millennium House
Brunel Drive
Newark NG24 2DE
UK
Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334
Email: infoeurope@genieind.com


Distributed By:

Effective Date: January, 2008. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex® is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie® is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. © 2008 Terex Corporation.

GS90RT 3.5K 0108H. Part No. 109352

www.genieindustries.com

Specifications



| MODELS | GS™-3390 RT | | GS™-4390 RT | | GS™-5390 RT | |
|---|----------------|---------|----------------|---------|---------------|---------|
| MEASUREMENTS | US | Metric | US | Metric | US | Metric |
| Working height maximum* | 39 ft | 12.06 m | 49 ft | 15.11 m | 59 ft | 18.15 m |
| A Platform height maximum | 33 ft | 10.06 m | 43 ft | 13.11 m | 53 ft | 16.15 m |
| B Platform height - stowed** | 5 ft 1 in | 1.55 m | 5 ft 11 in | 1.80 m | 6 ft 7.5 in | 2.02 m |
| C Platform length: | | | | | | |
| outside, extended - single deck | 13 ft .5 in | 3.98 m | 13 ft .5 in | 3.98 m | 13 ft .5 in | 3.98 m |
| outside, extended - dual deck | 17 ft 6.25 in | 5.34 m | 17 ft 6.25 in | 5.34 m | 17 ft 6.25 in | 5.34 m |
| D | 21 ft 6.5 in | 6.57 m | 21 ft 6.5 in | 6.57 m | 21 ft 6.5 in | 6.57 m |
| E Slide-out platform extension deck - front | 5 ft | 1.52 m | 5 ft | 1.52 m | 5 ft | 1.52 m |
| F Slide-out platform extension deck - rear | 4 ft | 1.22 m | 4 ft | 1.22 m | 4 ft | 1.22 m |
| G Platform width - outside | 6 ft | 1.83 m | 6 ft | 1.83 m | 6 ft | 1.83 m |
| H Height: | | | | | | |
| stowed | 8 ft 10.5 in | 2.71 m | 9 ft 7.5 in | 2.93 m | 10 ft 4 in | 3.15 m |
| stowed - rails lowered | 6 ft 7.75 in | 2.03 m | 7 ft 4.75 in | 2.25 m | 8 ft 1.25 in | 2.47 m |
| I Length - stowed: | | | | | | |
| single deck | 12 ft 11.25 in | 3.94 m | 12 ft 11.25 in | 3.94 m | ----- † | ----- |
| dual deck | 13 ft .5 in | 3.98 m | 13 ft .5 in | 3.98 m | ----- | ----- |
| with outriggers | 16 ft | 4.88 m | 16 ft | 4.88 m | 16 ft | 4.88 m |
| Length - extended: | | | | | | |
| single deck | 17 ft 8.5 in | 5.40 m | 17 ft 8.5 in | 5.40 m | 17 ft 8.5 in | 5.40 m |
| dual deck | 21 ft 6.5 in | 6.57 m | 21 ft 6.5 in | 6.57 m | 21 ft 6.5 in | 6.57 m |
| J Width: | | | | | | |
| standard tires | 7 ft 6 in | 2.29 m | 7 ft 6 in | 2.29 m | 7 ft 6 in | 2.29 m |
| high flotation tires | 8 ft 5 in | 2.57 m | 8 ft 5 in | 2.57 m | 8 ft 5 in | 2.57 m |
| K Wheelbase | 9 ft 4 in | 2.84 m | 9 ft 4 in | 2.84 m | 9 ft 4 in | 2.84 m |
| L Ground clearance - center | 1 ft 2 in | .36 m | 1 ft 2 in | .36 m | 1 ft 2 in | .36 m |



Collé Rental & Sales offers a Super Dual-Deck model with a platform length of 4.80 - 7.30 meters.

| PRODUCTIVITY | | | | | | |
|---|--------------|------------|--------------|------------|--------------|------------|
| Maximum platform occupancy*** | 7 | 7 | 7 | 7 | 6 | 6 |
| Lift capacity | 2,500 lbs | 1,134 kg | 1,500 lbs | 680 kg | 1,500 lbs | 680 kg |
| Lift capacity - extension deck | 500 lbs | 227 kg | 500 lbs | 227 kg | 500 lbs | 227 kg |
| Drive height | full height | | full height | | 30 ft | 9.14 m |
| Drive speed - stowed | 5.0 mph | 8.0 km/h | 5.0 mph | 8.0 km/h | 5.0 mph | 8.0 km/h |
| Drive speed - raised | 0.7 mph | 1.1 km/h | 0.7 mph | 1.1 km/h | 0.7 mph | 1.1 km/h |
| Gradeability - stowed**** | 50% | | 50% | | 40% | |
| Maximum outrigger leveling: front to back | 7° | | 7° | | 7° | |
| side to side | 12° | | 12° | | 12° | |
| Turning radius - inside | 7 ft 1 in | 2.16 m | 7 ft 1 in | 2.16 m | 7 ft 1 in | 2.16 m |
| Turning radius - outside | 17 ft 6 in | 5.33 m | 17 ft 6 in | 5.33 m | 17 ft 6 in | 5.33 m |
| Controls | proportional | | proportional | | proportional | |
| Drive | four wheel | | four wheel | | four wheel | |
| Raise / lower speed | 45 / 29 sec | | 45 / 39 sec | | 55 / 49 sec | |
| Tires - foam-filled rough terrain | 12 x 33 in | 30 x 84 cm | 12 x 33 in | 30 x 84 cm | 12 x 33 in | 30 x 84 cm |

| POWER | | | | | | |
|---------------------------|---|---------|---------|---------|---------|---------|
| Power source | Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW) Deutz F3L-2011 3 cylinder diesel 49 hp (36 kW), air cooled | | | | | |
| Auxiliary Power unit | 12 V DC | | 12 V DC | | 12 V DC | |
| Fuel tank capacity | 30 gal | 113.6 L | 30 gal | 113.6 L | 30 gal | 113.6 L |
| Hydraulic system capacity | 30 gal | 113.6 L | 30 gal | 113.6 L | 30 gal | 113.6 L |

| WEIGHT***** | | | | | | |
|-------------|------------|----------|------------|----------|------------|----------|
| | 12,085 lbs | 5,482 kg | 13,086 lbs | 5,936 kg | 16,616 lbs | 7,537 kg |

STANDARDS COMPLIANCE ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

*The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 **Based on RT tires. Deduct 2 in (5.8 cm) for high flotation air-filled and non-marking tires.
 ***GS-5390 CE/AUS market limited to 4 person platform occupancy.
 ****Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 *****Weight will vary depending on options and/or country standards.
 † GS-5390 comes standard with outriggers. Machine length with outriggers represents overall length.
www.genieindustries.com