

SEMI-INDUSTRIAL HANDLING SOLUTIONS

MSI 2 to 5 T series



MANITOU

MSI 40 T / 50 T EVOLUTION

MASTED FORKLIFT TRUCK



CAPACITY

MSI 40T

MSI 50T

Capacity

4000 kg

5000 kg

LOAD CENTRE

Load centre

500 mm

600 mm

TYRES

Front tyres

315/70 R22.5 154/150L RHS

Rear tyres

225/75 R15 XZM

ENGINES

Engine

PERKINS 1104D-44T (65/70 kW) Euro 3 A

LIFTING

Standard lifting height

3700 mm

DIMENSIONS

Height of protective roof

2440 mm

Length up to front face of forks

3294 mm

3384 mm

Overall Width

1732 mm

Aisle width with 800 x 1,200 pallet

4956 mm

5241 mm

Turning circle

2865 mm

2950 mm

EQUIPMENT

- Closed cab with tinted windows
- Cloth-covered seat
- Adjustable steering column
- Heating
- Rear/front wipers and front screen washer
- Right- and left-hand side door mirrors
- Rear road lighting
- Cross lever with built-in reversing shift
- Load shock absorber
- Electro-hydraulic cab lift
- Washer/wiper for rooflight
- Sun blind for rooflight
- Differential lock

