HYDRAULIC WINCH




SUSPENDED LOADS handling solutions


ADVANTAGES

- Turns your telehandler into a crane.
- Estremely fast implementation on the MANITOU carriage.
- Easy steering from the cab or with the machine's remote control (optional).
- Fast and accurate movements.

TECHNICAL CHARACTERISTICS

- Hydraulic motor+ end of cable automatic movement stop.
- Oil immersed negative break.
- Double or quadruple line pull (accoding to type).
- Homologated swivel self locking hook.
- Winch strorage stand with sleeves for fork handling.





	Capacity (kg)	Line pull	Total cable length (m)	Cable layers	E	ø	Max. hook speed m.s ⁻¹	Weight (kg)
Winch 3T	3000	1	49	3	24,5	10	24	395
Winch 4T	4000	1	51	3	25,5	12	21,5	510
Winch 5T	5000	1	51	3	25,5	12	21,5	510
Winch 7,2T	7200	1	76	3	35	14	19,4	700
Winch 9T	9000	1	30	2	18	16	22,5	850
Winch 12T	12000	2	60	3	10	16	21,5	1185
Winch 18T	18000	2	56	2	28	18	12	1550
Winch 22T	22000	2	56	2	28	18	12	1550

COMPATIBILITY*

	Winch 3T	Winch 4T	Winch 5T	Winch 7,2T
Part number MT	885236	N/A	N/A	N/A
MT 835	Χ			
MT 1135	Χ			
MT 1335	X			
Part number MRT	708534	711933	N/A	N/A
MRT EASY (€ 3A)	Χ	X		
Part number MRT+	921337	921338	921341	934500
MRT EASY (€ 3B)	X	X		
MRT + PRIV	Χ	X	X	
MRT 3255				X
	Winch 9T	Winch 12T	Winch 18T	Winch 22T
Part number MHT	939030	710405	675308	909011
MHT 790	Χ			
MHT 1490	Χ			
MHT 10120		X		
MHT 10180			X	
MHT 10225				X

^{*} This Attachment has been approved for the machines listed above. A load chart Machine/Attachment has been created accordingly

This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document.

Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes

